

Datasheet SM-76 Antenna

Mechanical Data:

Size in mm (LxWxH)	58x48x15
Weight	63gram without cable
Cabel	5m RG174/U Standard, other length on request
Pulling Strength	6kg for 5 sec. With molded plastics on connector end for strain relief
Connector available	BNC, TNC, FME, MMCX, MCX, SMA, SMB or SMC in straight or right angle type
Optional	Universal Connector Adapter (FME to TNC, BNC, SMA, SMB, MCX)
Mounting	magnetic & screw mount

Gain	26 dB min
Noise Figure	2.0 max
Axel Ratio	3 dB max.
VSWR	2.0 max
Output Impedance	50Ω

Contact us:

TecSys GmbH

Karl-Theodor-Str. 55

80803 Munich

Germany

Email: mark@tecsys.de

Internet: <http://www.tecsys.de>

Phone: +49 89 321 990 14

Fax: +49 89 307 21 65

Environmental Conditions:

Operating Temp.	-40°C ~ + 85°C
Storage Temp.	-40°C ~ + 85°C
Relative Humidity	95% non-condensing
Water resistance	100% Waterproof

Antenna Element:

Polarization	R.H.C.P:
Absolute Gain	+ 5dBi typical
Gain @ 10° Elevation	-1 dBi typical
Axel Ratio	3 dB max

Low Noise Amplifier:

Power Gain	28 dB typical
Bandwidth	2 MHz min
Noise Figure	1.5 max
Supply Voltages	+2.5 ~+5.5 (2.5~8.0) V DC
Current Consumption	12mA+/-2mAat 3.~5 VDC

Overall Performance:

(Antenna element, LNA & Coax cable)

Center Frequency	1575.42
------------------	---------

