






GPS and GSM combination Antenna Guide

A combination of both GPS and GSM antennas that are designed mainly to simplify the need for an AVL or Fleet Management.




Features:

- Low Noise Figure
- Fully Waterproof
- Ultra-High sensitive
- Excellent Temperature Stability

Quad-Band Antenna AU-Series:

					
Model:	AU-3C	AU-3S	AU-4C	AU-4S	AU-7
Ø in mm (DxH)	64,5x14	64,5x13,6	63x15,6	63x15,6	50,2x12.2
Overall Gain	27dB	26dB	27dB	27dB	27 dB
Supply Volts	2.7~5.5VDC	2.7~5.5VDC	3~5.5VDC	3.0~5.5VDC	3.0~5.5VDC
Current	13mA	13 mA	12 mA	12 mA	10~12mA
Operation - temperature	-40 °C~+85 °C	-40 °C ~ +85 °C	-40 °C ~ +80 °C	-40 °C~+80 °C	-40 °C~80 °C

Quad-Band Antenna AW-Series:

			
Model:	AW-3C	AW-4C	AW-4S
Ø in mm (DxH)	64,5x19	63x15,6	63x15,6
Overall Gain	26 dB	27 dB	27 dB
Supply Volts	3~5.5VDC	3 ~ 5.3VDC	3 ~5.5VDC
Current	11 mA	6 mA	12 mA
Operation - temperature	-40 °C~+55 °C	-40 °C ~ +80 °C	-40 °C ~ +80 °C