

OmniDrive USB2.0 LF Professional

- ❑ Universal PC Card drive for USB 2.0
- ❑ For Linear Flash, SRAM, ATA Flash and ATA Hard Disk
- ❑ Easy installation and handling
Win 98/Me, 2000, XP, Vista, Win7 & Linux
- ❑ Compact, robust aluminum casing
- ❑ Option: -40 to +85 °C operating temperature



OmniDrive USB 2.0 LF is an external drive for a lot of **Memory Cards** complying with the PC Card Standard. Specially for **Linear Flash Cards, ATA Flash Cards, ATA Hard Disks, SRAM Cards** as well as Compact-Flash, SmartMedia, MultiMediaCards and SD Cards with adapter. The compact aluminum casing offers perfect protection for device and card. The power supply comes from the USB bus itself. In addition, if necessary, also by means of an AC adapter.

Modern future-proof design

OmniDrive USB 2.0 LF is based on a flexible design, that is perfect for industrial needs.

For **OmniDrive USB 2.0 LF** this means in detail:

- **High Speed data transfer through USB 2.0**
- **Extreme functional and data security**, on account of longstanding experience with OmniDrive Centronics and varying PC Cards
- **Flexibility and protection of investment** by easy update possibility
- **Long-term availability.**
- **Option:** Extended temperature range
- 40 °C to + 85 °C

Applications

OmniDrive USB 2.0 LF is perfect for industrial applications where Linear Flash Cards are used.

OmniDrive USB 2.0 LF

OmniDrive USB 2.0 LF supports besides **Linear Flash Cards** also SRAM Cards and ATA memory media. The device drivers allow to use the well-tried Professional software tools.

The Windows tool **PC Card Manager** offers extensive possibilities for access to Linear Flash Cards:

- ✓ **Hex-Editor and Binary Copy Utility**
- ✓ **Test of data consistence** by 16-bit CRC checksum
- ✓ **Linear Flash Erase Utility**

*The universal programming interface (API) offers by a DLL **direct access to Memory Cards from own customized Windows applications.** Detailed information can be found in the optionally available PC Card Software Development Kit.*

Linux software support

Under Linux **OmniDrive USB 2.0 LF** is usable as a **Plug and Play** drive for ATA Flash Cards. For this the device drivers of Linux are used.

Mounting version

For use in customer projects **OmniDrive USB LF** is also available as **3 1/2" mounting version**. The **compact metal frame** is just 128 mm long and 25 mm high. It can be used also under conditions with restricted space.

Specification *OmniDrive USB 2.0 LF*

Item	<i>OmniDrive USB 2.0 LF</i>
PC Card Slots	1x type II front slot
Interface	USB 2.0
PC Card Types	Linear Flash ¹⁾ , SRAM, ATA Flash, ATA Hard Disk, CompactFlash, SmartMedia, MultiMedia, Secure Digital Cards, a.o. with adapter
Software	Professional Software with utilities: PC Card Manager (PCM) OmniCtrl, BCPY32, CSMFORM
Dimensions (W x H x D)	109 mm x 35 mm x 135 mm
Weight	approx. 300 g
Operating Temperature	0°C to +70°C ²⁾
Non-operating Temperature	-20°C to +85°C ²⁾
Humidity	max. 90% (not condensing)
Power Supply	DC 5 V from PC via USB bus optional additional power supply via AC adapter
System Requirements	PC with Win 98/Me, Win 2000, Win XP, Vista, Win7 & Linux ³⁾
Conformity	CE

¹⁾ AMD, Catalyst, Fujitsu, Intel Series 1, 2, 2+, StrataFlash etc. Others on request.

²⁾ Optional -40°C to +85°C (operating and non-operating).

³⁾ Other operating systems on request.

Shipping Contents:

OmniDrive USB LF

- **OmniDrive USB LF** in aluminum case
- **USB cable**
- **CD with Professional Software:**
32-bit device driver for Win 98/Me, 2000, XP, Vista Win7 & Vista
PC Card Manager 32-bit utility for format-independent data access inclusive HEX-Editor
32-bit API with DeviceloControl-Interface
- **User manual** in multi-language

Additional products:

- **PC Card SDK**
(PC Card Software Development Kit) for direct access to a Memory Card's contents using own applications
API-32, DLLs and **code examples**

Options:

- **AC adapter** (Euro and US)