

SATADOM

R & L Type High Profile

-Embedded Flash Storage-

- ❑ Kapazität von 128MB bis 8GB
- ❑ Es ist ein Industrie Qualitätsprodukt mit integriertem ECC (Error Correction Code)
- ❑ Lese.- Schreibgeschwindigkeit von 24 MB/s / 14MB/s
- ❑ Einfach & leicht zu installieren
- ❑ VCC ist eingebaut auf Pin 7
- ❑ Hoch qualitatives & innovatives Design gegen Vibrazion



Specifications:

Capabilities:	128 MB ~ 8 GB	ECC Technology	Built in ECC corrects up to 8-bit per 512 Byte
Interface:	Serial ATA I	MTBF:	>3,000,000 hours
Transfer Rate:	PIO Mode 0-4	R/W Endurance:	2,000,000 times
	MwDMA mode 0-2	Wear-Leveling:	Support
	Ultra DMA Mode 0-2	DC Input Voltage:	+5V single Power supply operation
Burst Speed Rate:	150 MB/sec	Power consumption	200mA (max.)
Data Transfer Rate:	Read: 24MB/sec. (max) Write 14 MB/sec.	Enclosure Material	PC mechanical cover and UL-94
Operation Temp:	0°C~+70°C (Standard) -40°C~+85°C (Industrial)	Dimensions:	25x39.4x6.5 (WxLxH)
Storage Temp:	-55°C ~ + 95°C	Weight:	10+/-3g
Humidity:	10% ~ 95 % non-condensing	Certificate:	CE, FCC, RoHS
Vibration:	5G (7~2000Hz)		
Shock:	50G/10ms		