

CH0706S Chassis Type Monitor / Touch



Specification:

Panel:	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide Screen / 7" viewable diagonal area
	Active Area / Pixel Pitch	152.40(H)x91.44(V)mm / 0.1905 (H)x0.1905 (V) mm
	Native Res. / Colors	800 (H) x 480 (V) / 262 K
	Brightness / Contrast	400 cd/m2 (typ) / 300:1
	Response Time	< 16 ms
	Viewing Angle	H. 120° (-60° ~ + 60°), V. 100° (-60° ~ + 40°)
	Light Source	CCFL, Long Life 50.000 hrs (typ)
	Audio System	2 x 2W speaker
Input Terminals:	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
Convenient Features:	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm)	
Power:	External AC-to-12VDC power adapter w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
Power cons.	Operation / Power	12 watt, < 2 watt (Support DPMS)
Op. Condition	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
Storage Condition:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
Certification:	FCC, CE	
Dimensions:	Physical (without base)	W x H x D = 182.6 x 125.0 x 59.2 mm
	Carton	W x H x D = 246 x 237 x 131 mm
Weight:	N.W. / G.W	2.0 kg / 3.0 kg
Options:	Touch Technology	Resistive, SAW, Capacitive, Multi Touch
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)