

CH1705S Chassis Type Monitor / Touch



Specification:

Panel:	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	4:3 or Wide / 17" viewable diagonal area
	Active Area / Pixel Pitch	337.92(H)x270.34 (V)mm / 0.264 (H)x0.264 (V) mm
	Native Res. / Colors	1280 (H) x 1024 (V) / 16.7 Million
	Brightness / Contrast	300 cd/m2 (typ) / 800 : 1
	Response Time	< 5 ms
	Viewing Angle	H. 160° (-80° ~ + 80°), V. 160° (-80° ~ + 80°)
	Light Source	CCFL, Long Life 50.000 hrs (typ)
	Audio System	2 x 2W Speaker
Input Terminals:	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
Convenient Features:	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm)	
Power:	Internal Power supply w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
Power cons.	Operation / Power	30 watt, < 2 watt (Support DPMS)
Op. Condition	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
Storage Condition:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
Certification:	FCC, CE	
Dimensions:	Physical (without base)	W x H x D = 379.7 x 318.4 x 59.8 mm
	Carton	W x H x D = 416 x 425 x 142 mm
Weight:	N.W. / G.W	5.0 kg / 6.0 kg
Options:	Touch Technology	Resistive, SAW, Capacitive.
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)