

## CH2555S Wide Screen Chassis Type Monitor / Touch



### Specification:

<b>Panel:</b>	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide Screen / 25.54" viewable diagonal area
	Active Area / Pixel Pitch	550.08(H)x 343.80(V)mm/0.2865 (H)x0.2865(V) mm
	Native Res. / Colors	1920 (H) x 1200 (V) / 16.7 Million
	Brightness / Contrast	350 cd/m2 (typ) / 1500:1
	Response Time	< 8 ms
	Viewing Angle	H. 178° (-89° ~ + 89°), V. 178° (-89° ~ + 89°)
	Light Source	CCFL, Long Life 50.000 hrs (typ)
	Audio System	2W Amplifier x 2
<b>Input Terminals:</b>	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
<b>Convenient Features:</b>	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 400 x 200 mm )	
<b>Power:</b>	External AC-to-12VDC power adapter w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
<b>Power cons.</b>	Operation / Power	95 watt, < 2 / 5watt (Support DPMS)
<b>Op. Condition</b>	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
<b>Storage Condition:</b>	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
<b>Certification:</b>	FCC, CE	
<b>Dimensions:</b>	Physical (without base)	W x H x D = 620.0 x 414.0 x 93.0 mm
	Carton	W x H x D = TBD
<b>Weight:</b>	N.W. / G.W	12.0 kg / 13.5 kg
<b>Options:</b>	Touch Technology	SAW, Capacitive, IR-Multi Touch
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)