

CH4604S Wide Screen Chassis Type Monitor / Touch



Specification:

Panel:	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide Screen / 46" viewable diagonal area
	Active Area / Pixel Pitch	1018.08(H)x 572.67(V)mm / 0.53 (H) x 0.53(V) mm
	Native Res. / Colors	1920 (H) x 1200 (V) 16.7 Million
	Brightness / Contrast	450 cd/m2 (typ) / 5000:1
	Response Time	< 8 ms
	Viewing Angle	H. 178° (-89° ~ + 89°), V. 178° (-89° ~+ 89°)
	Light Source	CCFL, Long Life 50.000 hrs (typ)
	Audio System	3W Amplifier x 2
Input Terminals:	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
Convenient Features:	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 600 x 300 mm)	
Power:	External AC-to-12VDC power adapter w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
Power cons.	Operation / Power	190 watt, < 2 watt (Support DPMS)
Op. Condition	Temperature / Humidity	0 °C ~ 50 °C, 10% ~ 90% (no condensation)
Storage Condition:	Temperature / Humidity	-20 °C ~ 60 °C, 10% ~ 90% (no condensation)
Certification:	FCC, CE	
Dimensions:	Physical (without base)	W x H x D = 1132.0 x 676.0 x 180.0 mm
	Carton	W x H x D = BD
Weight:	N.W. / G.W	38.0 kg / 41.0 kg
Options:	Touch Technology	IR-Multi Touch
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)