

## CH5205S Chassis Type Monitor / Touch



### Specification:

<b>Panel:</b>	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 52" viewable diagonal area
	Active Area / Pixel Pitch	1152 (H) x 648 (V)mm / 0.6 (H)x0.6(V) mm
	Native Res. / Colors	1920 (H) x 1080 (V) / 16.7 Million
	Brightness / Contrast	500 cd/m2 (typ) / 1500 : 1 HD or Optional FHD
	Response Time	< 6 ms
	Viewing Angle	H. 176° (-88° ~ + 88°), V. 176° (-88° ~ + 88°)
	Light Source	CCFL, Long Life 50.000 hrs (typ)
	Audio System	2 x 3W Speaker
<b>Input Terminals:</b>	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
<b>Convenient Features:</b>	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 600 x 400 mm )	
<b>Power:</b>	Internal Power supply w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
<b>Power cons.</b>	Operation / Power	300 watt, < 5 watt (Support DPMS)
<b>Op. Condition</b>	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
<b>Storage Condition:</b>	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
<b>Certification:</b>	FCC, CE	
<b>Dimensions:</b>	Physical (without Base)	W x H x D = 1267 x 762.5 x 131 mm
	Carton	W x H x D = TBD
<b>Weight:</b>	N.W. / G.W	42 kg / 45 kg
<b>Options:</b>	Touch Technology	Resistive, SAW, Capacitive & IR-Multi Touch
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)