

OF10W16D Wide Screen Open Frame Monitor / Touch



Specification:

Panel:	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 10.1" viewable diagonal area
	Active Area / Pixel Pitch	222.72 (H) x 125.28 (V)/0.2175 (H) x 0.2088 (V) mm
	Native Res. / Colors	1024 (H) x 600 (V) / 262 K
	Brightness / Contrast	200 cd/m2 (typ) / 650:1
	Response Time	< 10 ms
	Viewing Angle	H. 90° (-45° ~ + 45°), V. 65° (-45° ~ + 20°)
	Light Source	LED light source, Long Life 35.000 hrs (typ)
	Audio System	2W Amplifier
Input Terminals:	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
Convenient Features:	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm)	
Power:	External AC-to-12VDC power adapter w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
Power cons.	Operation / Power	3 watt, < 1 watt (Support DPMS)
Op. Condition	Temperature / Humidity	0 °C ~ 50 °C, 10% ~ 90% (no condensation)
Storage Condition:	Temperature / Humidity	-20 °C ~ 60 °C, 10% ~ 90% (no condensation)
Certification:	FCC, CE	
Dimensions:	Physical	WxHxD=270,0x182 (ScrewCentertoCen.) x 50.0 mm
	Carton	WxHxD = TBD
Weight:	N.W. / G.W	2.5 kg / 3.5 kg
Options:	Touch Technology	Resistive + Anti Vandal Glass, Projected Capacitive
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)