

## OF12W05D Wide Screen Open Frame Monitor / Touch



### Specification:

<b>Panel:</b>	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 12.1" viewable diagonal area
	Active Area / Pixel Pitch	261.12 (H) x 163.20 (V)/0.204 (H) x 0.204 (V) mm
	Native Res. / Colors	1280 (H) x 800 (V) / 262 K
	Brightness / Contrast	450 cd/m2 (typ) / 350:1
	Response Time	< 15 ms
	Viewing Angle	H. 130° (-65° ~ + 65°), V. 115° (-65° ~ + 50°)
	Light Source	CCFL light source, Long Life 50.000 hrs (typ)
	Audio System	2W Amplifier
<b>Input Terminals:</b>	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
<b>Convenient Features:</b>	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm)	
<b>Power:</b>	External AC-to-12VDC power adapter w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
<b>Power cons.</b>	Operation / Power	20 watt, < 1 watt (Support DPMS)
<b>Op. Condition</b>	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
<b>Storage Condition:</b>	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
<b>Certification:</b>	FCC, CE	
<b>Dimensions:</b>	Physical	WxHxD=312,0x224 (ScrewCentertoCen.) x 56.0 mm
	Carton	WxHxD = TBD
<b>Weight:</b>	N.W. / G.W	3.0 kg / 4.0 kg
<b>Options:</b>	Touch Technology	Resistive , Saw + Anti Vandal Glass, Capacitive
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)