

## OF19W05D Wide Screen Open Frame Monitor / Touch



### Specification:

<b>Panel:</b>	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 19" viewable diagonal area
	Active Area / Pixel Pitch	408.24 (H) x 255.15 (V) / 0.284(H) x 0.284 (V) mm
	Native Res. / Colors	1440 (H) x 900 (V) / 16.7 Million
	Brightness / Contrast	300 cd/m2 (typ) / 1000:1
	Response Time	< 5 ms
	Viewing Angle	H. 170° (-85° ~ + 85°), V. 160° (-80° ~ + 80°)
	Light Source	CCFL light source, Long Life 50.000 hrs (typ)
	Audio System	2W Amplifier
<b>Input Terminals:</b>	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
<b>Convenient Features:</b>	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 100 x 100 mm )	
<b>Power:</b>	External AC-to-12VDC power adapter w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
<b>Power cons.</b>	Operation / Power	30 watt, < 2 watt (Support DPMS)
<b>Op. Condition</b>	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
<b>Storage Condition:</b>	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
<b>Certification:</b>	FCC, CE	
<b>Dimensions:</b>	Physical	WxHxD=455,0x318.1(ScrewCentertoCen.) x 65 mm
	Carton	WxHxD = 490 x 426 x 160 mm
<b>Weight:</b>	N.W. / G.W	5.5 kg / 6.5 kg
<b>Options:</b>	Touch Technology	Resistive, Saw + Anti Vandal Glass, Capacitive, IR-Multi Touch
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)