

OF 2205D Open Frame Monitor / Touch



Specification:

| | | |
|-----------------------------|--|--|
| Panel: | Cell Type / Glass Surf. | TFT LCD / Black Anti-Glare, low reflection coating |
| | Aspect Ratio / Size | Wide / 22" viewable diagonal area |
| | Active Area / Pixel Pitch | 473.8(H)x296.1 (V)mm / 0.282 (H)x0.282 (V) mm |
| | Native Res. / Colors | 1680 (H) x 1050 (V) / 16.7 Million |
| | Brightness / Contrast | 300 cd/m2 (typ) / 1000 : 1 |
| | Response Time | < 5 ms |
| | Viewing Angle | H. 170° (-85° ~ + 85°), V. 160° (-80° ~ + 80°) |
| | Light Source | CCFL, Long Life 50.000 hrs (typ) |
| | Audio System | 2W Amplifier |
| Input Terminals: | 1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P. | |
| Convenient Features: | Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 100 x 100 mm) | |
| Power: | Internal Power supply w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz | |
| Power cons. | Operation / Power | 36 watt, < 2 watt (Support DPMS) |
| Op. Condition | Temperature / Humidity | 0°C ~ 50°C, 10% ~ 90% (no condensation) |
| Storage Condition: | Temperature / Humidity | -20°C ~ 60°C, 10% ~ 90% (no condensation) |
| Certification: | FCC, CE | |
| Dimensions: | Physical (with Flanges) | WxHxD=520x358.7 (Screw Center to C.) x 65 mm |
| | Carton | WxHxD = 556 x 450 x 160 mm |
| Weight: | N.W. / G.W | 7.5 kg / 8.5 kg |
| Options: | Touch Technology | Resistive, SAW, Capacitive. |
| | Enhanced Panel | Panel with LED backlight, High Brightness & Sun Light Readable |

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)