

OF25W55D Wide Screen Open Frame Monitor / Touch



Specification:

Panel:	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 25.54" viewable diagonal area
	Active Area / Pixel Pitch	550.08 (H) x 343.80 (V) / 0.2865(H) x 0.2865(V) mm
	Native Res. / Colors	1920 (H) x 1200 (V) / 16.7 Million
	Brightness / Contrast	350 cd/m2 (typ) / 1500:1
	Response Time	< 8 ms
	Viewing Angle	H. 178° (-89° ~ + 89°), V. 178° (-89° ~ + 89°)
	Light Source	CCFL light source, Long Life 50.000 hrs (typ)
	Audio System	2W Amplifier
Input Terminals:	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
Convenient Features:	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 400 x 200 mm)	
Power:	External AC-to-12VDC power adapter w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
Power cons.	Operation / Power	95 watt, < 2 watt (Support DPMS)
Op. Condition	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
Storage Condition:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
Certification:	FCC, CE	
Dimensions:	Physical	WxHxD=617,0x427.0(ScrewCentertoCen.) x 92 mm
	Carton	WxHxD = 617 x 411 x 92 mm
Weight:	N.W. / G.W	12 kg / 13.5 kg
Options:	Touch Technology	Resistive, Saw + Anti Vandal Glass, Capacitive, IR-Multi Touch
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)