

OF46W04D Wide Screen Open Frame Monitor / Touch



Specification:

| | | |
|-----------------------------|--|--|
| Panel: | Cell Type / Glass Surf. | TFT LCD / Black Anti-Glare, low reflection coating |
| | Aspect Ratio / Size | Wide / 46" viewable diagonal area |
| | Active Area / Pixel Pitch | 1018,08 (H) x 572.67 (V) / 0.53(H) x 0.53(V) mm |
| | Native Res. / Colors | 1920 (H) x 1080 (V) / 16.7 Million |
| | Brightness / Contrast | 450 cd/m2 (typ) / 5000 : 1 |
| | Response Time | < 8 ms |
| | Viewing Angle | H. 178° (-89° ~ + 89°), V. 178° (-89° ~ + 89°) |
| | Light Source | CCFL light source, Long Life 50.000 hrs (typ) |
| | Audio System | 3W Amplifier |
| Input Terminals: | 1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P. | |
| Convenient Features: | Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 600 x 300 mm) | |
| Power: | External AC-to-12VDC power adapter w´ universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz | |
| Power cons. | Operation / Power | 190 watt, < 2 watt (Support DPMS) |
| Op. Condition | Temperature / Humidity | 0°C ~ 50°C, 10% ~ 90% (no condensation) |
| Storage Condition: | Temperature / Humidity | -20°C ~ 60°C, 10% ~ 90% (no condensation) |
| Certification: | FCC, CE | |
| Dimensions: | Physical | WxHxD=1129x691(ScrewCentertoGen.)x177.5 mm |
| | Carton | WxHxD = 1129 x 673 x 177.5 mm |
| Weight: | N.W. / G.W | 38 kg / 41 kg |
| Options: | Touch Technology | IR-Multi Touch |
| | Enhanced Panel | Panel with LED backlight, High Brightness & Sun Light Readable |

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)