

## Open Frame Monitor with Touch

### 12" / 15" / 17" / 19"

- ❑ LCD Panel size from 12" to 19"
- ❑ Resistive, Capacitive or SAW Touch
- ❑ USB and RS232 Dual Port available
- ❑ Speaker or Non speaker Choice
- ❑ Mounting Options :
  - 3 M compatible (Side)
  - VESA Standard (Back)
  - 75 x 75 mm & 100 x 100mm
- ❑ High Resolution & Brightness



### **Applications:**

The Monitors are supplied as open frame units and have multiple mounting options. They are ideal for applications in harsh environment such Production areas, kiosks, machines, cabinets, doors, construction vehicles etc...

### **Flexible Use:**

The industrial monitors consist of very high quality. Depending on the customers application they can be even further adapted.

Standardly the Monitors are equipped with high resolution and very durable TFT displays and Resistive Touch, SAW or Capacitive Touch.

### **Informationen & Angebot :**

#### **TecSys GmbH**

Karl-Theodor-Str. 55  
80803 Munich / Germany

Email: [mark@tecsys.de](mailto:mark@tecsys.de)

Internet: <http://www.tecsys.de>

Phone: +49 89 321 990 14

Fax: +49 89 307 21 65

## Specification: T06-Open Frame Series

<b>Model Name:</b>	<b>T06-12OF</b>	<b>T06-15OF</b>	<b>T06-17OF</b>	<b>T06-19OF</b>
<b>LCD Panel</b>	TFT Active Matrix LCD Display			
<b>Resolution:</b>	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024
<b>Brightness:</b>	250 cd / m <sup>2</sup>	250 cd / m <sup>2</sup>	300 cd / m <sup>2</sup>	300 cd / m <sup>2</sup>
<b>Contrast Ratio:</b>	300 : 1	600 : 1	1000 : 1	1000 : 1
<b>Band with:</b>	135 MHz	108 MHz	135 MHz	135 MHz
<b>Display Color:</b>	12 M	16.7M	16.7M	16.7M
<b>Pixel Pitch:</b>	0.307x0.307 mm	0.297x0.297 mm	0.264x0.264 mm	0.294 x 0.294 mm
<b>Response Time:</b>	Tr/tf: 5/11 ms	Tr/tf: 2/6 ms	Tr/tf: 1.3/3.7 ms	Tr/tf: 1.3/3.7 ms
<b>System Memory</b>	H: 90° V: 65°	H: 160° V: 160°	H: 160° V: 160°	H: 178° V: 178°
<b>Backlight Life</b>	50,000 hours			
<b>OSD features</b>	Auto tune, Brightness, Contrast, Clock, Phase, H-position, V-position, Recall			
<b>Input Signal</b>	Analog RGB (VGA), DVI Optional			
<b>Touch Technology</b>	5 Wires Resistive, Capacitive, SAW			
<b>Touch Interface</b>	USB, RS232 or USB & RS 232 Dual Ports			
<b>Touch Active Area (W/H)</b>	246.0x184.5 mm <sup>2</sup>	304.1x228.0 mm <sup>2</sup>	337.92x270.3 mm <sup>2</sup>	377.30x302.05 mm <sup>2</sup>
<b>Storage Conditions</b>	0°C – 40°C (32°F-104°F) 10%-80% (No Condensation)			
<b>Operating Environment</b>	-20°C – 60°C (-4°F-140°F) 10%-90% (Non Condensation)			
<b>Dimensions</b>	350x48.5x250 mm	40x55.5x300m m	442x62x320m m	497x76x383m m
<b>N.W / G.W</b>	2.8 kg / 4.0 kg	5.0kg / 6.0kg	6.6kg / 7.5kg	7.5kg / 8.5kg
<b>Touch Screen Type</b>	Side:3M Compatible, Back: VESA 75x75mm, 100x100mm			
<b>Power Consumption</b>	<25W	<30W	<40W	<45W
<b>Power Supply</b>	Adapter Input 100-240V AC, 50-60Hz 1.5A; Adapter Output 12V DC, 4.16 A			
<b>Warranty</b>	One Year panel warranty, 2 Years Part and Labor Warranty			
<b>Environment: EMC &amp; Safety</b>	FCC Class A, CD, LVD			

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)

March 1, 2010