

## PM1205 Wide Screen Panel Mount Monitor / Touch



### Specification:

|                             |                                                                                                                                        |                                                                |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Panel:</b>               | Cell Type / Glass Surf.                                                                                                                | TFT LCD / Black Anti-Glare, low reflection coating             |
|                             | Aspect Ratio / Size                                                                                                                    | Wide / 12.1" viewable diagonal area                            |
|                             | Active Area / Pixel Pitch                                                                                                              | 261.1(H) x 163.2 (V)mm / 0.204(H) x 0.204(V) mm                |
|                             | Native Res. / Colors                                                                                                                   | 1280 (H) x 800 (V) / 262 K                                     |
|                             | Brightness / Contrast                                                                                                                  | 400 cd/m2 (typ) / 350 : 1                                      |
|                             | Response Time                                                                                                                          | < 15 ms                                                        |
|                             | Viewing Angle                                                                                                                          | H. 130° (-65° ~ + 65°), V. 115° (-65° ~ + 50°)                 |
|                             | Light Source                                                                                                                           | CCFL, Long Life 50.000 hrs (typ)                               |
|                             | Audio System                                                                                                                           | 2 x 2W Speaker                                                 |
| <b>Input Terminals:</b>     | 1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.                                                              |                                                                |
| <b>Convenient Features:</b> | Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B)<br>OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm ) |                                                                |
| <b>Power:</b>               | Internal Power supply w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz                                                          |                                                                |
| <b>Power cons.</b>          | Operation / Power                                                                                                                      | 18 watt, < 1 watt (Support DPMS)                               |
| <b>Op. Condition</b>        | Temperature / Humidity                                                                                                                 | 0°C ~ 50°C, 10% ~ 90% (no condensation)                        |
| <b>Storage Condition:</b>   | Temperature / Humidity                                                                                                                 | -20°C ~ 60°C, 10% ~ 90% (no condensation)                      |
| <b>Certification:</b>       | FCC, CE                                                                                                                                |                                                                |
| <b>Dimensions:</b>          | Physical                                                                                                                               | W x H x D = 380 x 280 x 59.0 mm                                |
|                             | Carton                                                                                                                                 | W x H x D = TBD                                                |
| <b>Weight:</b>              | N.W. / G.W                                                                                                                             | 4.0 kg / 5.0 kg                                                |
| <b>Options:</b>             | Touch Technology                                                                                                                       | Resistive, SAW, Capacitive, IR-Multi Touch.                    |
|                             | Enhanced Panel                                                                                                                         | Panel with LED backlight, High Brightness & Sun Light Readable |

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)