

## PM1205 Panel Mount Monitor / Touch



### Specification:

<b>Panel:</b>	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	4:3 or Wide / 12.1" viewable diagonal area
	Active Area / Pixel Pitch	246.0 (H)x184.5 (V)mm / 0.3075 (H)x0.3075 (V) mm
	Native Res. / Colors	800 (H) x 600 (V) / 262 K or op. 1024 x 768
	Brightness / Contrast	400 cd/m2 (typ) / 600:1 or op. 450 cd/m2 / 700:1
	Response Time	< 35 ms
	Viewing Angle	H. 140° (-70° ~ + 70°), V. 120° (-60° ~ + 60°)
	Light Source	CCFL, Long Life 50.000 hrs (typ)
	Audio System	2 x 2W Speaker
<b>Input Terminals:</b>	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.	
<b>Convenient Features:</b>	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm )	
<b>Power:</b>	External AC-to-12VDC power adapter w' universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
<b>Power cons.</b>	Operation / Power	22 watt, < 2 watt (Support DPMS)
<b>Op. Condition</b>	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
<b>Storage Condition:</b>	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
<b>Certification:</b>	FCC, CE	
<b>Dimensions:</b>	Physical	W x H x D = 360 x 285 x 58 mm
	Carton	W x H x D = TBD
<b>Weight:</b>	N.W. / G.W	3.5 kg / 4.5 kg
<b>Options:</b>	Touch Technology	Resistive, SAW, Capacitive, IR Multi Touch.
	Enhanced Panel	Panel with LED backlight, High Brightness & Sun Light Readable

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)