

POF 0576 Open Frame Panel-PC (Fanless)



Specification:

Panel:	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	4:3 / 5.7" viewable diagonal area	
	Active Area / Pixel Pitch	115.2 (H) x 86.4 (V) mm / 0.18 (H) x 0.18 (V) mm	
	Native Res. / Colors	640 (H) x 480 (V) / 262 K	
	Brightness / Contrast	400 cd/m ² (typ) / 800:1	
	Response Time	< 25 ms	
	Viewing Angle	H. 120° (-60° ~ + 60°), V. 100° (-40° ~ + 60°)	
	Light Source	CCFL, Long Life 50.000 hrs (typ)	
	System:	CPU	Intel Atom N270 1.6 GHz or Core 2 Duo
Bios		Award 16 Mb SPI BIOS	
System / Graphic Chipset		Intel 945 GSE + ICH7-M system Chipset / integrated Graphic Media Accelerator 950	
System Memory		1 x 200 SO-DIMM up to 2 GB single channel DDR2 533 SDRAM, non-ECC	
HDD (Storage)		2 x SATA, 1 x EIDE, 1x CF	
I / Ports		2 x RJ 45 Gigabit Ethernet LAN ports	
		1 x VGA	
		4 x RS232 (2x RS232 internal) (9P D-Sub male)	
	6 x USB 2.0 (2 x USB 2.0 internal)		
	2 x PS2 (1 x keyboard, 1 x mouse)		
	1 x Audio Jack (MIC-in, Line-in, Line-out)		
	Expansion	1 x PCI, 1 x Mini-PCIe	
Power	Power Input	12V DC-IN (Lockable connector)	
	Power Consumption	50W (typ)	
	Temperature / Humidity	0 °C ~ 50 °C, 10% ~ 90% (no condensation)	
Dimensions	Physical	W x H x D = TBD (mm)	
Certification:	FCC, CE		
Options:	Resistive, SAW, Capacitive, Multi –Touch, WiFi , LED backlight		

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten) May 2010