

PPC Industrial Panel PC 12" / 15" / 17"

- ❑ Economical and reliable
- ❑ High quality - 4: 3 TFT active matrix LCD Panel
- ❑ ATOM N270 1.6 GHz / 1G DDRII / 160 GB HDD or 32 GB SATA DOM
- ❑ Spill proof, Water resistant, Dust Proof - IP 65 / NEMA 4
- ❑ Resistive, SAW & Capacitive Touch
- ❑ VESA 75 x75 or 100 x100 mm
- ❑ Left & Right / Top & Bottom brackets



Applications:

The Monitors are supplied as Chassis Type units and have multiple mounting options (Panel brackets and VESA). They are ideal for applications in harsh environment such Production areas, kiosks, machines, cabinets, doors, construction vehicles etc...

Flexible Use:

The Industrial Monitors consist of very high quality. Depending on the customers application they can be even further adapted.

Standardly the Monitors are equipped with high resolution and very durable TFT LCD Displays and Resistive Touch, SAW or Capacitive Touch.

Informationen & Angebot :

TecSys GmbH

Karl-Theodor-Str. 55

80803 Munich / Germany

Email: mark@tecsys.de

Internet: <http://www.tecsys.de>

Phone: +49 89 321 990 14

Fax: +49 89 307 21 65

Specification: PPC 12 – 17” Industrial Panel PC

Model Name:	PPC-12”	PPC-15”	PPC-17”
LCD Panel :	TFT Active Matrix LCD Display		
Resolution:	1024 x 768@75Hz	1024 x 768@75Hz	1280 x 1024@85Hz
Brightness:	200 cd / m2	250 cd / m2	250 cd / m2
Touch Technology	5 Wires Resistive, Capacitive, SAW		
Audio	Audio AC’97 2.0 Complaint, Built –in 2x 2 W Speakers		
CPU	ATOM N270 1.6 GHz		
Chipset	North Bridge Intel 945 GSE Express Chipset South Bridge Intel ICH 7		
System Memory	1 x SO - DIMM Memory Slot (Supports up to 2 GB)		
OS Support	Windows 2000 / NT / XP / VISTA / Win 7, Embedded XP, WEPOS, LINUX		
HDD	2.5” SATA (up to 1 TB) or SATA DOM (16 GB or 32 GB)		
Compact Flash	1 x Slot Compact Flash Type II		
I/O Port Serial	4 x Serial (3 x External, 1 x Internal)		
I/O Port Parallel	1 x DB-25, Female, Support EPP / ECP		
USB	2 x USB 2.0 bottom / 2 x USB 2.0 side / 1 x USB 2.0 Internal for Touch Controller / 3 x USB 2.0 Internal Reserved		
PS / 2 Mouse	1 x 6-Pin Mini DIN		
PS / 2 Keyboard	1 x 6-Pin Mini DIN		
LAN	Support 100 / 1000 BASE-T Ethernet		
VGA	1 x DB – 15, Female		
DC Jack	1 x Mic In, 1 x Audio Out		
Expansion	1 x Mini PCI-E Slot (Internal Slot for Wireless and Bluetooth)		
Color	Black		
Storage Conditions	-20°C to 60°C 20%-80% RH (No Condensation)		
Operating Environment	05°C to 35°C		
Dimensions (L x W x H)	310x250x68 mm	350x280x68 mm	424x340x85 mm
N.W / G.W	6.5 kg / 8.5 kg	6.9 kg / 8.5 kg	6.9 kg / 8.5 kg
Touch Screen Type	Back: VESA 75x75mm, 100x100mm Left & Right or Top & Bottom brackets		
Power Input	External Adapter 12V DC, Maximum 120 W		
Warranty	One Year Panel warranty, 2 Years Part and Labor Warranty		
Environment: EMC & Safety	FCC Class A, CD, LVD		

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten)

August , 2010