

PPM 1905 Panel Mount - PC (w' Fan & Fanless)



Specification:

Panel:	Cell Type / Glass Surf.	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	4:3 / 19" viewable diagonal area	
	Active Area / Pixel Pitch	376.32(H) x 301.06 (V) mm / 0.294(H) x 0.294(V)	
	Native Res. / Colors	1280 (H) x 1024 (V) / 16.7 Million	
	Brightness / Contrast	300 cd/m2 (typ) / 800 :1	
	Response Time	< 5 ms	
	Viewing Angle	H. 160° (-80° ~ + 80°), V. 160° (-80° ~ + 80°)	
	Light Source	CCFL, Long Life 50.000 hrs (typ)	
	System:	CPU	Intel Atom N270 1.6 GHz or Core 2 Duo
Bios		Award 16 Mb SPI BIOS	
System / Graphic Chipset		Intel 945 GSE + ICH7-M system Chipset / integrated Graphic Media Accelerator 950	
System Memory		1 x 200 SO-DIMM up to 2 GB single channel DDR2 533 SDRAM, non-ECC	
HDD (Storage)		2 x SATA, 1 x EIDE, 1x CF	
I / Ports			2 x RJ 45 Gigabit Ethernet LAN ports
			1 x VGA
			4 x RS232 (2x RS232 internal) (9P D-Sub male)
			6 x USB 2.0 (2 x USB 2.0 internal)
			2 x PS2 (1 x keyboard, 1 x mouse)
Expansion		1 x Audio Jack (MIC-in, Line-in, Line-out)	
		1 x PCI, 1 x Mini-PCIe	
Power	Power Input & Cons.	24V DC-IN (4-Din connector) / 65 W (typ)	
	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)	
Dimensions	Physical	W x H x D = TBD (mm)	
Certification:		FCC, CE	
Options:		Resistive, SAW, Capacitive, Multi –Touch, WiFi , LED backlight	

(Errors & Changes are reserved / Irrtümer & Änderungen vorbehalten) May 2010