

# Omni Drive USB 2.0 LF Professional

- □ Universal USB-2 PC Card reader/writer
- ☐ For Linear Flash, SRAM, ATA Flash, ATA Hard Disk
- □ Easy installation and operation Win 98/Me, 2000, XP, Vista, Win 7, Win10 & Linux
- ☐ Compact, robust aluminium enclosure
- ☐ Option: -40°C ~ +85°C operating temp.

Omni*Drive USB LF* is an external drive for a large number of Memory Card types corresponding to the PC Card Standard. In particular, for **Linear Flash Cards, SRAM Cards, ATA Flash Cards**, **ATA Hard Disks**.

Using an appropriate adapter, you can also read/write CompactFlash, SmartMedia and MultiMediaCards.

The compact aluminium housing offers protection to both the card and the unit itself.

Operating current is drawn from the USB-port itself, though an external power-supply (extra) may also be used.

## Modern future-proof Design

**Omni***Drive* **USB 2.0 LF** *is* based on a flexible design concept to meet industrial requirements.

This means for the Omni*Drive USB 2.0 LF* in practice:

- High-speed data transfer via USB 2.0
- Extreme functional reliability and data security
- Flexibility and protection of investment by easy update facility
- Long-term availability by own FPGA design

## Application areas

**Omni***Drive USB 2.0 LF* is ideally suited to industrial applications, especially where Linear Flashcards are to be processed.



## OmniDrive USB 2.0 LF

Besides **Linear Flash Cards**, the Omni*Drive USB* 2.0 LF also supports PC SRAM Cards und ATA media.

The drivers make possible the use of the triedand-tested **Professional Software Tools**.

The Windows Tool **PC Card Manager** offers extensive facilities for accessing Linear Flash Cards:

- Hex-Editor und Binary Copy Utility
- Test of data consistency by 16-bit CRC checksum.
- > Linear Flash Erase Utility

The universal programming interface (API) offers direct access to Memory Cards by DLL from your own customised Windows applications. For this, the PC Card Software Development Kit is available as a separate product.

## Software support under Linux

Under Linux, the OmniDrive USB 2.0 LF operates as a **Plug and Play** drive for ATA Flash Cards using the Linux drivers.

#### **Build-in version**

For use in custom products, the Omni*Drive USB LF* is also available as a **3** ½" **frame version.** This is just 128 mm long and 25,5 mm high, and therefore takes up very little space.

TecSys GmbH 
■ Tel (089) 321 990-0 
■ www.tecsys.de



# Specifications OmniDrive USB 2.0 LF

Description	Omni <i>Drive USB 2.0LF</i>
Memory Card Slots:	1 x PCMCIA Typ II front-slot
Data interface:	USB 2.0 and USB 1.1
Memory Card Types in PC Slot:	PC Linear Flash, SIEMENS FMC-xx Flash Cards, PC SRAM, PC ATA Flash.  With adapter: CompactFlash, SmartMedia, MultiMedia, SD, microSD etc.
Software:	Professional Software with the utilities: PC Card Manager (PCM) OmniCtrl, BCPY32, CSMFORM
Dimensions (B x H x T) :	109 mm x 35 mm x 135 mm
Weight:	ca. 300 g
Operating temperature:	0°C ~ +70°C <sup>2)</sup>
Storage temperature:	-20°C ~ +85°C <sup>2)</sup>
Humidity:	max. 90% (non-condensing)
Power supply:	DC 5 V from PC via USB-port. Optional additional power-supply via AC adapter (extra)
System requirements:	PC with Win 98/Me, Win 2000, Win XP, Vista, Win 7, Win10 or Linux <sup>3)</sup>
Conformity:	(€

# **Shipping contents:**

- Omni Drive USB 2.0 LF in table-top housing
- USB-cable 2m
- CD with Professional Software:
   32-bit drivers for Win 98/Me, 2000, XP,
   Vista, Win 7, Win10 & Linux
   PC Card Manager 32-bit utility for format independent data-access including hex-editor.
- 32-bit API with DeviceloControl interface
- Multilingual user manual

## **Options:**

• AC power-adapter (Euro and US.)

OMNIDRIVEUSB2P-LF\_DB\_EN\_20200807\_RH

# **Additional products:**

- PC Card SDK
   (PC Card Software Development Kit) for direct access to Memory Cards for custom applications.
- API-32, DLLs and code examples
- Memory Cards

TecSys GmbH 
■ Tel (089) 321 990-0 
■ www.tecsys.de