

CM5504-QF35L0 Chassis Mount 55" Monitor 3840 x 2160

- Built-in fans to improve system cooling allows up to 24-hours a day usage
- Optional built-in touch screen for interactive applications
- Optional auto-brightness sensor offers application by day and night
- Optional with different frames (Open Frame, Chassis Type, Panel Mount, Rack Mount)



Specifications

Panel:	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 55" viewable diagonal area	
	Active Area / Pixel Pitch	1209.6 (H) x 680.4 (V) / 0.315(H) x 0.315(V) mm	
	Native Res. / Colors	3840 (H) x 2160 (V) / 16.7 Million	
	Brightness / Contrast	350 cd/m2 (typ) / 4000:1	
	Response Time	< 7 ms (G to G)	
	Viewing Angle	H. 178° (-89° ~ + 89°), V. 178° (-89° ~+ 89°)	
	Light Source	LED, Long Life 35.000 hrs (typ)	
Input Sources:	Audio System	2W Speaker x 2	
Input Terminals:	1 x VGA, 5 x HDMI, 1 x DP, 1x PC Audio (Stereo headphone Jack) 1 x DC Power Plug		
Convenient Features:	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 650 x 400 mm)		
Power:	Internal power supply with universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz		
Power cons.	Operation / Power	160 watt / < 1 watt (Support DPMS)	
Operation:	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)	
Storage:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)	
Dimensions:	Physical	See drawing	
	Carton	WxHxD = TBD	
Weight:	N.W. / G.W	43.5 kg / 46.5 kg	
Options:	Touch Infrared Touch	Enhanced Panel	Others
		Protection Glass High Brightness Wide Temperature Sunlight Readable 1920 x 1080 resolution	Digital Signage Motion Sensor Light Sensor Auto-Dimming SV+AV, DVI, HDMI

Full-size drawing available on request!

