

## CH0656 Chassis Type Monitor / Touchmonitor

- **Modular mechanical design provides flexible product configuration and easy maintenance**
- **Optional built-in touch screen for interactive applications**
- **Optional auto-brightness sensor offers application by day and night**
- **Also with different frames (Chassis Mount, Open Frame, Panel Mount, Rack Mount) available**



Specifications			
<b>Panel:</b>	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	4:3 / 6.5" viewable diagonal area	
	Active Area / Pixel Pitch	132.48 (H) x 99.36 (V) / 0.207 (H) x 0.207 (V) mm	
	Native Res. / Colors	640 (H) x 480 (V) / 262 K	
	Brightness / Contrast	400 cd/m2 (typ) / 500:1	
	Response Time	< 25 ms	
	Viewing Angle	H. 140° (-70° ~ + 70°), V. 120° (-60° ~+ 60°)	
	Light Source	LED, Long Life 35.000 hrs (typ)	
<b>Input Sources:</b>	Audio System	2W Speaker x 2	
<b>Input Terminals:</b>	1 x VGA (15 Pin F.D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC P. P.		
<b>Convenient Features:</b>	Auto Calibration, back light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm )		
<b>Power:</b>	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz		
<b>Power cons.</b>	Operation / Power	10 watt, < 2 watt (Support DPMS)	
<b>Operating:</b>	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)	
<b>Storage:</b>	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)	
<b>Dimensions:</b>	Physical	WxHxD = 176.6 x 132.6 x 49.2 mm	
	Carton	WxHxD = 325 x 330 x 135 mm	
<b>Weight:</b>	N.W. / G.W	2.0 kg / 3.0 kg	
<b>Options:</b>	<b>Touch</b>	<b>Enhanced Panel</b>	<b>Others</b>
	Resistive Touch Capacitive Touch SAW Touch Infrared Touch Protection Glass	High Brightness Wide Temperature Sunlight Readable	Digital Signage Motion Sensor Light Sensor Auto-Dimming SV+AV, DVI, HDMI

