

## FM1855-WX Flush Mount 18,5" Monitor 1366x768

- Modular mechanical design provides flexible product configuration and easy maintenance
- Optional built-in touch screen for interactive applications
- Optional auto-brightness sensor offers application by day and night
- Optional with different frames (Open Frame, Chassis Type, Chassis Mount, Rack Mount etc.)



### Specifications

<b>Panel:</b>	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 18,5" viewable diagonal area	
	Active Area / Pixel Pitch	409.8 (H) x 230.4 (V) / 0.3(H) x 0.3(V) mm	
	Native Res. / Colors	1366 (H) x 768 (V) / 16.7 Million	
	Brightness / Contrast	250 cd/m2 (standard) / 1000:1	
	Response Time	< 5 ms	
	Viewing Angle	H. 170° (-85° ~ + 85°), V. 160° (-80° ~+ 80°)	
	Light Source	LED, Long Life 35.000 hrs (typ)	
<b>Input Sources:</b>	Audio System	2W Amplifier	
<b>Input Terminals:</b>	1 x VGA (15 Pin Female D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC Power Plug		
<b>Convenient Features:</b>	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm )		
<b>Power:</b>	Internal power supply with universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz		
<b>Power cons.</b>	Operation / Power	18 watt, < 1 watt (Support DPMS)	
<b>Operating temp.:</b>	Temperature / Humidity	0°C ~ 50°C / 10% ~ 90% (no condensation)	
<b>Storage temp.:</b>	Temperature / Humidity	-20°C ~ 60°C / 10% ~ 90% (no condensation)	
<b>Dimensions:</b>	Physical	WxHxD = TBD	
	Carton	WxHxD = TBD	
<b>Weight:</b>	N.W. / G.W	6.5 kg / 7.5 kg	
<b>Options:</b>	<b>Touch</b>	<b>Enhanced Panel</b>	<b>Others</b>
	Resistive Touch	Protection Glass	Digital Signage
	Capacitive Touch	High Brightness	Motion Sensor
SAW Touch	Wide Temperature	Light Sensor	
	Sunlight Readable	Auto-Dimming	
		SV+AV, DVI, HDMI etc.	

Full-size drawing available on request!

