

FCH2705-WH30L0 Monitor / Touchmonitor

- Modular mechanical design provides flexible product configuration and easy maintenance
- Optional built-in touch screen for interactive applications
- Optional auto-brightness sensor offers application by day and night
- Stainless steel enclosure IP66 all round



Specifications			
Panel:	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 27" viewable diagonal area	
	Active Area / Pixel Pitch	597.89 (H) x 336.31 (V) mm / 0.3114(H) x 0.3114(V) mm	
	Native Res. / Colors	1920 (H) x 1080 (V) / 16.7 Million	
	Brightness / Contrast	300 cd/m2 (typ) / 1000:1	
	Response Time	< 5 ms	
	Viewing Angle	H. 170° (-85° ~ + 85°), V. 160° (-80° ~+ 80°)	
	Light Source	LED, Long Life 35.000 hrs (typ)	
Input Sources:	Audio System	N/A	
Input Terminals:	1 x DC Power Plug , 1 x VGA (15 Pin Female D-SUB) (Standard)		
Convenient Features:	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 100 x 100 mm)		
Power:	12V DC in, universal / Auto-Sensing ext. Adapter AC 90 to 260 V, 50 / 60 Hz		
Power cons.	Operation / Powersaving	42.5 watt / < 1 watt (Supports DPMS)	
Operation:	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)	
Storage:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)	
Dimensions:	Physical	WxHxD = please see drawing	
	Carton	TBD	
Weight:	N.W. / G.W	12 Kgs / 13.5 Kgs	
Options:	Touch	Enhanced Panel	Others
	Resistive Touch Capacitive Touch SAW Touch Infrared Touch Protection Glass	High Brightness Wide Temperature Sunlight Readable	Digital Signage (Standalone) Digital Signage (Networked) Light Sensor Motion Sensor SV+AV, DVI, HDMI etc.

Errors and omissions excepted!

Full-size drawing available on request

