

OF1505 Open Frame Monitor / Touchmonitor

- **Modular mechanical design provides flexible product configuration and easy maintenance**
- **Optional built-in touch screen for interactive applications**
- **Optional auto-brightness sensor offers application by day and night**
- **Optional with different frames (Chassis Mount, Chassis Type, Panel Mount, Rack Mount)**



Specifications

Panel:	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	4:3 / 15" viewable diagonal area	
	Active Area / Pixel Pitch	304.12 (H) x 228.10 (V) / 0.297 (H) x 0.297 (V) mm	
	Native Res. / Colors	1024 (H) x 768 (V) / 16.2 M	
	Brightness / Contrast	250 cd/m2 (typ) / 500:1 Standard	
	Response Time	< 12 ms	
	Viewing Angle	H. 130° (-65° ~ + 65°), V. 100° (-55° ~+ 45°)	
	Light Source	LED, Long Life 35.000 hrs (typ)	
Input Sources:	Audio System	2W Amplifier	
Input Terminals:	1 x VGA (15 Pin Female D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC Power Plug		
Convenient Features:	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm)		
Power:	Optional Internal power supply with universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz		
Power cons.	Operation / Power	20 watt, < 2 watt (Support DPMS)	
Operating:	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)	
Storage:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)	
Dimensions:	Physical	With Flanges: WxHxD = 345,3 x 282 x 58 (mm)	
		Without Flanges: WxHxD = TBD	
	Carton	WxHxD = 419 x 380 x 142 (mm)	
Weight:	N.W. / G.W	4 kg / 5 kg	
Options:	Touch	Enhanced Panel	Others
	Resistive Touch	High Brightness	Digital Signage
	Capacitive Touch	Wide Temperature	Motion Sensor
	SAW Touch	Sunlight Readable	Light Sensor
	Infrared Touch		Auto-Dimming
Protection Glass		SV+AV, DVI, HDMI	

