

OF1705 Open Frame 17" Monitor, 1280x1024

- **Modular mechanical design provides flexible product configuration and easy maintenance**
- **Optional built-in touch screen for interactive applications**
- **Optional auto-brightness sensor offers application by day and night**
- **Optional with different frames (Chassis Mount, Chassis Type, Panel Mount, Rack Mount)**



Specifications			
Panel:	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	5:4 / 17" viewable diagonal area	
	Active Area / Pixel Pitch	337.92 (H) x 270.34 (V) / 0.264 (H) x 0.264 (V) mm	
	Native Res. / Colors	1280 (H) x 1024 (V) / 16.7 M	
	Brightness / Contrast	250 cd/m2 (typ) / 800:1	
	Response Time	< 5 ms	
	Viewing Angle	H. 170° (-85° ~ + 85°), V. 160° (-80° ~ + 80°)	
	Light Source	LED, Long Life 35.000 hrs (typ)	
Input Sources:	Audio System	Option: 2W Amplifier	
Input Terminals:	1 x VGA (15 Pin Female D-SUB) 1 x DVI, 1x PC Audio (Stereo headphone Jack) 1 x DC Power Plug		
Convenient Features:	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm)		
Power:	Internal power supply with universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz		
Power cons.	Operation / Power	33 watt, < 2 watt (Support DPMS)	
Operating:	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)	
Storage:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)	
Dimensions:	Physical	With Flanges: WxHxD = 377,3 x 328 x 58,8 (mm)	
		Without Flanges: WxHxD = see drawing	
	Carton	WxHxD = 416 x 425 x 142 (mm)	
Weight:	N.W. / G.W	5 kg / 6 kg	
Options:	Touch	Enhanced Panel Options	Others
	Resistive Touch	High Brightness	Digital Signage
	Capacitive Touch	Wide Temperature	Motion Sensor
	SAW Touch	Sunlight Readable	Light Sensor
Infrared Touch	Protection Glass	Auto-Dimming	SV+AV, DVI, HDMI

Full size drawing available on request

