

OF5504-QF35L0 Open Frame 55" Monitor 3840 x 2160

- Built-in fans to improve system cooling allows up to 24-hours a day usage
- Optional built-in touch screen for interactive applications
- Optional auto-brightness sensor offers application by day and night
- Optional with different frames (Chassis Mount, Chassis Type, Panel Mount, Rack Mount)



Specifications		
Panel:	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 55" viewable diagonal area
	Active Area / Pixel Pitch	1209.6 (H) x 680.4 (V) / 0.315(H) x 0.315(V) mm
	Native Res. / Colors	3840 (H) x 2160 (V) / 16.7 Million
	Brightness / Contrast	350 cd/m2 (typ) / 4000:1
	Response Time	< 7 ms (G to G)
	Viewing Angle	H. 178° (-89° ~ + 89°), V. 178° (-89° ~+ 89°)
	Light Source	LED, Long Life 35.000 hrs (typ)
Input Sources:	Audio System	2W Speaker x 2
Input Terminals:	1 x VGA, 5 x HDMI, 1 x DP, 1x PC Audio (Stereo headphone Jack) 1 x DC Power Plug	
Convenient Features:	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 650 x 400 mm)	
Power:	Internal power supply with universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz	
Power cons.	Operation / Power	160 watt / < 1 watt (Support DPMS)
Operation:	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)
Storage:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)
Dimensions:	Physical	With Flanges: WxHxD = 1355.6 x 822.4 x 176.8 mm Without Flanges: WxHxD = 1328.4 x 795 x 176.8 mm
	Carton	WxHxD = TBD
Weight:	N.W. / G.W	43.5 kg / 46.5 kg
Options:	Touch	Enhanced Panel
	Infrared Touch	Protection Glass High Brightness Wide Temperature Sunlight Readable
		Others Digital Signage Motion Sensor Light Sensor Auto-Dimming SV+AV, DVI, HDMI

Full-size drawing available on request!

