

PM1505 Panel Mount Monitor / Touchmonitor

- Modular mechanical design provides flexible product configuration and easy maintenance
- Optional built-in touch screen for interactive applications
- Optional auto-brightness sensor offers application by day and night
- Optional with different frames (Open Frame, Chassis Type, Chassis Mount, Rack Mount)



Specifications			
Panel:	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	4:3 / 15" viewable diagonal area	
	Active Area / Pixel Pitch	304.12 (H) x 228.10.5 (V) / 0.297 (H) x 0.297 (V) mm	
	Native Res. / Colors	1024 (H) x 768 (V) / 16.2 M	
	Brightness / Contrast	250 cd/m2 (typ) / 700:1	
	Response Time	< 35 ms	
	Viewing Angle	H. 140° (-70° ~ + 70°), V. 120° (-60° ~+ 60°)	
	Light Source	LED, Long Life 35.000 hrs (typ)	
Input Sources:	Audio System	N/A	
Input Terminals:	1 x VGA (15 Pin Female D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC Power Plug		
Convenient Features:	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 75 x 75 mm)		
Power:	Internal power supply with universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz		
Power cons.	Operation / Power	20 watt, < 2 watt (Support DPMS)	
Operating:	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)	
Storage:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)	
Dimensions:	Physical	WxHxD = 410 x 335 x 64 (mm)	
	Carton	WxHxD = 419 x 380 x 142 (mm)	
Weight:	N.W. / G.W	5 kg / 6 kg	
Options:	Touch	Enhanced Panel	Others
	Resistive Touch	High Brightness	Digital Signage
	Capacitive Touch	Wide Temperature	Motion Sensor
SAW Touch	Sunlight Readable	Light Sensor	
Infrared Touch	Protection Glass	Auto-Dimming	
			SV+AV, DVI, HDMI

