

RM1045

Rack Mount Monitor 10,4"

- **Modular mechanical design provides flexible product configuration and easy maintenance**
- **Optional built-in touch screen for interactive applications**
- **Optional auto-brightness sensor offers application by day and night**
- **Optional with different frames (Open Frame, Chassis Type, Chassis Mount, Panel Mount)**



Specifications

Panel:	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect ratio / Size	4:3 / 10.4" Viewing area	
	Native Res. / Colors	800 (H) x 600 (V) / 262 K	1024(H) x 768(V) / 16.2M
	Active Area / Pixel Pitch	211.2 (H) x 158.4 (V) / 0.264 (H) x 0.264 (V) mm	210.4 (H) x 157.8 (V) / 0.206 (H) x 0.206 (V) mm
	Response Time	< 35 ms	< 25 ms
	Viewing Angle	H. 140° (-70° ~ +70°) V. 120° (-60° ~ +70°)	H. 160° (-80° ~ +70°) V. 140° (-70° ~ +70°)
	Brightness / Contrast	350 cd/m2 (typ) / 600:1	
	Light Source	LED, Long Life 35.000 hrs (typ)	
	Input Sources:	Audio System	2W Speaker x 2
Input Terminals:	1 x VGA (15 Pin Female D-SUB) 1x PC Audio (Stereo headphone Jack) 1 x DC Power Plug		
Convenient Features:	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi Languages, Wall Mount Ready (VESA 100 x 100 mm)		
Power:	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260 V, 50 / 60 Hz		
Power cons.	Operation / Power	18 watt, < 2 watt (Support DPMS)	
Operating:	Temperature / Humidity	0°C ~ 50°C, 10% ~ 90% (no condensation)	
Storage:	Temperature / Humidity	-20°C ~ 60°C, 10% ~ 90% (no condensation)	
Dimensions:	Physical	WxHxD = 482 x 220 x 68 (mm)	For 19" Rack 5U
	Carton	WxHxD = TBD	
Weight:	N.W. / G.W	4 kg / 5 kg	
Options:	Touch	Enhanced Panel	Others
	Resistive Touch Capacitive Touch SAW Touch	Protective glass High Brightness Wide Temperature Sunlight Readable	Digital Signage Motion Sensor Light Sensor Auto-Dimming SV+AV, DVI, HDMI

